

Cleaning Procedure

Drain Cleaning - Forming and Packing Areas							
Application:		Турі	Typical residues:				
Drain cleaning		Mixt	Mixture of oil, plastic, dust.				
Specific application area: Drain cleaning		General information:					
		foar <u>cont</u>	Clean out of production hours using low pressure foaming equipment. <u>Care should be taken not to</u> <u>contaminate equipment with spray when</u> <u>cleaning the drains.</u>				
Cleaning frequency: Weekly							
Cleaning Procedure & Chemicals	%	°C	min.	Notes			
Cleaning Preparation				Remove products from the production area. Remove pallets, trays and packaging.			
				Lift off drain covers and lay next to drain.			
Remove coarse soil				Gather waste with a squeegee or broom and deposit in waste bin.			
Pre-rinsing - Water		40 - 60		Rinse with low pressure in the direction of the drain.			
Collect residues				Collect waste with a squeegee. Deposit any waste in a bin. Remove waste bins.			
Safety Boots or Wellington Boots must be wornSafety gloves be wornImage: Comparison of the c							

Document Reference **Drain Cleaning Procedure QMR 044** Revision 1 10th May 2017 Owned by: Production Manager Authorised By: Operations Manager





Cleaning Procedure						
Alkaline Cleaning	2 - 4	40 - 60	20 - 30	Foam from bottom to top. A minimum contact time of 20 minutes is needed to loosen deposits. Scrub drain covers and drain channel after foaming with 4% Solution of foam using scrubbing broom		
Intermitted rinse Water		40 - 60		Remove deposits by rinsing with low pressure from top to bottom.		
Cleanliness check				Check all areas. Re-clean if necessary.		
Neutral Disinfection	1 - 3	40 - 60	20 - 30	Disinfect from top to bottom. Treat <u>all</u> surfaces completely with the disinfectant.		
Store cleaning tools				To prevent cross-contamination, rinse all cleaning tools and hang on the correct rack.		

